



ME-1000-WPTU
ME-2000-WPTU
ME-3000-WPTU

ME-6000-WPTU
ME-10000-WPTU

ONLINE UPS



ME-6000-WPTU
ME-10000-WPTU

ME-3000-WPTU

ME-2000-WPTU

ME-1000-WPTU

Features

- True double-conversion online UPS
- Wide input voltage range (110-300 VAC)
- Input power factor correction 0.99
- Output power factor 0.8
- Converter mode available
- ECO mode operation for energy saving (only available for 1-3KVA)
- Generator compatible
- Adjustable battery numbers only available for 6K and up models
- Smart SNMP works well with either USB or RS-232 together
- Emergency power off function only available for 6K and up models

MODEL	ME-1000-WPTU	ME-2000-WPTU	ME-3000-WPTU	ME-6000-WPTU	ME-10000-WPTU
PHASE	Single phase with ground				
CAPACITY	1000 VA / 800 W	2000 VA / 1600 W	3000 VA / 2400 W	6000 VA / 4800 W	10000 VA / 8000 VA
INPUT					
Voltage Range	Low Line Transfer	160 VAC/140 VAC/120 VAC/110 VAC ± 5% (Ambient Temp.<35°C) (based on load percentage 100% - 80 % / 80 % - 70 % / 70 - 60 % / 60 % - 0)		176 VAC ± 3% @ 100% load 110 VAC ± 3% @ 50% load	
	Low Line Comeback	175 VAC /155 VAC/ 135 VAC /125 VAC± 5 % (Ambient Temp.<35°C) (based on load percentage 100% - 80 % / 80 % - 70 % / 70 - 60 % / 60 % - 0)		186 VAC ± 3% @ 100% load 120 VAC ± 3% @ 50% load	
	High Line Transfer	300 VAC ± 5 %		300 VAC ± 3%	
	High Line Comeback	290 VAC ± 5 %		290 VAC ± 3%	
Frequency Range	40Hz ~ 70 Hz			46~54 Hz or 56~64 Hz	
Power Factor	≥ 0.99 @ nominal voltage			≥ 0.99 @ 100%load	
OUTPUT					
Output Voltage	200/208/220/230/240 VAC			208/220/230/240 VAC	
AC Voltage Regulation (Batt. Mode)	± 1%			± 1%	
Frequency Range (Synchronized Range)	47 ~ 53 Hz or 57 ~ 63 Hz			46~54 Hz or 56~64 Hz	
Frequency Range (Batt. Mode)	50 Hz ± 0.25 Hz or 60Hz ± 0.3 Hz			50 Hz ± 0.1 Hz or 60 Hz ± 0.1 Hz	
Current Crest Ratio	3:1			3:1	
Harmonic Distortion	≤ 3 % THD (Linear Load), ≤ 6% THD (non-linear load)			≤ 3 % THD (Linear Load) ≤ 5 % THD (Non-linear Load)	
Transfer Time	AC Mode to Batt. Mode	Zero			
	Inverter to Bypass	4 ms (Typical)			Zero
Waveform (Batt. Mode)	Pure Sinewave				
EFFICIENCY					
AC Mode	88%	89%	90%	92%	93%
Battery Mode	83%	87%	88%	90%	91%
BATTERY					
Battery Type	12 V / 9 Ah	12 V / 9 Ah	12 V / 9Ah	12 V / 9 Ah	12 V / 9 Ah
Numbers	2	4	6	16	16
Typical Recharge Time	4 hours recover to 90% capacity			9 hours recover to 90% capacity	
Charging Current (max.)	1.0 A			1.0 A / 2.0 A (adjustable)	
Charging Voltage	27.4 VDC ± 1%	54.7 VDC ± 1%	82.1 VDC ±1%	218.4 VDC ±1%	218.4 VDC ±1%
INDICATORS					
LCD Panel	UPS status, Load level, Battery level, Input/Output voltage, Discharge timer, and Fault conditions				
ALARM					
Battery Mode	Sounding every 4 seconds				
Low Battery	Sounding every second				
Overload	Sounding twice every second				
Fault	Continuously sounding				
PHYSICAL					
Dimension, D x W x H (mm)	282 x 145 x 220	397 x 145 x 220	421 x 190 x 318	369 x 190 x 688	442 x 190 x 688
Net Weight (kgs)	9.8	17	27.6	61	66
ENVIRONMENT					
Humidity	20-90 % RH @ 0- 40°C (non-condensing)			0-95 % RH @ 0- 50°C (non-condensing)	0-95 % RH @ 0- 40°C (non-condensing)
Noise Level	Less than 50dB @ 1 Meter			Less than 55dB @ 1 Meter	Less than 58dB @ 1 Meter
MANAGEMENT					
Smart RS-232/USB	Supports Windows 2000/2003/XP/Vista/ 2008, Windows 7/8, Linux, Unix, and MAC				
Optional SNMP	Power management from SNMP manager and web browser				

NOTE 1: Derate to 80% of capacity in CVCF mode or when the output voltage is adjusted to 200/208VAC.

NOTE 2: If the UPS is installed or used in a place where the altitude is above than 1000m, the output power must be derated one percent per 100m.

Distributed by

KL Consulting C3 Pty Ltd
Unit C3, Villa Ladera Complex
17 1st Avenue, Umdloti Beach
Durban, 4319
087 700 3771
084 459 1454



Uninterruptible Power Supply

BBONE 2400VA
BBONE 1200VA



BBONE-012S+ (Excl Battery)

**BBONE-024S+
(Excl Batteries)**

Features

- Simulated sine wave inverter
- Wide input voltage range
- 10 A or 20 A standard AC charging current
- LCD display for comprehensive information
- Overload, short circuit and reverse polarity protection

MODEL	BBONE-012S+	BBONE-024S+
	CAPACITY	1200VA/ 720W
INPUT		
Voltage	230 VAC	
Acceptable Voltage Range	90-280 VAC	
Frequency	50 Hz/60 Hz (Auto sensing)	
OUTPUT		
AC Voltage Regulation (Batt. Mode)	± 10%	
Efficiency (Peak)	82%	85%
Transfer Time	20 ms typical	
Waveform (Batt. Mode)	Simulated sine wave	
BATTERY		
Battery Type and Numbers	12 V 100Ah x 1 (*Optional)	12 V 100Ah x 2 (*Optional)
PROTECTION		
Full Protection	Overload, short circuit and polarity reserve protection	
PHYSICAL		
Dimension	368mm (W)x 309mm (D) x 396mm (H)	490mm (W)x 367mm (D) x 396mm (H)
OPERATING ENVIRONMENT		
Humidity	0 to 90% Relative Humidity(Non-condensing)	
Operating Temperature	0°C to 40°C	
Storage Temperature	-15°C to 50°C	

* Product specifications are subject to change without further notice

***NB BBone-012S+ / BBone-024S+ EXCLUDED Batteries**

KL Consulting C3 Pty Ltd
Unit C3, Villa Ladera Complex
17 1st Avenue, Umdloti Beach
Durban, 4319
087 700 3771
084 459 1454

